



O-Seal PipeThread Connector

UMOP



Connects Fractional Tube to Female NPT Thread

Part No.	Tube OD T		P (NPT)	Dimensions (mm)									
	inch	mm		E Min.	h		H		F	G	I	I ₁	L
UMOP-0202N	1/8	3.17	1/8	2.3	3/4	19.05	7/16	11.11	12.8	15.4	26.2	7.1	32.8
UMOP-0402N	1/4	6.35	1/8	4.8	3/4	19.05	9/16	14.28	15.1	17.4	27.7	7.1	35.1
UMOP-0404N	1/4	6.35	1/4	4.8	15/16	23.81	9/16	14.28	15.1	17.4	31.0	9.7	38.4
UMOP-0604N	3/8	9.52	1/4	7.0	15/16	23.81	11/16	17.46	16.7	18.9	32.5	9.7	39.9
UMOP-0606N	3/8	9.52	3/8	7.0	1-1/8	28.57	11/16	17.46	16.7	18.9	34.0	10.4	41.4
UMOP-0608N	3/8	9.52	1/2	7.0	1-5/16	33.33	11/16	17.46	16.7	18.9	39.6	13.5	47.0
UMOP-0808N	1/2	12.70	1/2	10.0	1-5/16	33.33	7/8	22.22	22.7	21.6	39.6	13.5	49.8
UMOP-1212N	3/4	19.05	3/4	16.0	1-1/2	38.10	1-1/8	28.57	24.4	21.9	42.2	14.2	52.3

ISO Tapered threads are available for all fractional UMOP. To order, add "R" as a suffix instead of "N".

Dimensions are for reference only and are subject to change without prior notice.
E is minimum opening. F, G and L are typical finger tight.