


AN Bulkhead Union

UBUA



Connects Fractional Tube to An Flared Tube

| Part No. | Tube OD | | AN Tube Flare Size | | Straight Thread P(U) | Dimensions (mm) | | | | | | | | | | | | | |
|------------|---------|-------|--------------------|-------|----------------------|-----------------|--------|-------|-------|-------|------|------|----------------|------|----------------|-----------------------|---------------------|--|--|
| | inch | mm | inch | mm | | E Min. | h | | H | | F | I | l ₁ | L | L ₁ | Panel Hole Drill Size | Max Panel Thickness | | |
| | | | | | | | inch | mm | inch | mm | | | | | | | | | |
| UBUA-0404S | 1/4 | 6.35 | 1/4 | 6.35 | 7/16-20 | 4.3 | 5/8 | 15.87 | 9/16 | 14.28 | 15.1 | 46.5 | 26.2 | 53.8 | 33.5 | 11.5 | 10.2 | | |
| UBUA-0606S | 3/8 | 9.52 | 3/8 | 9.52 | 9/16-18 | 7.0 | 3/4 | 19.05 | 11/16 | 17.46 | 16.7 | 49.8 | 29.5 | 57.2 | 36.8 | 14.7 | 11.2 | | |
| UBUA-0808S | 1/2 | 12.70 | 1/2 | 12.70 | 3/4-16 | 10.0 | 15/16 | 23.81 | 7/8 | 22.22 | 22.7 | 55.6 | 31.8 | 65.8 | 41.9 | 19.4 | 12.7 | | |
| UBUA-1212S | 3/4 | 19.05 | 3/4 | 19.05 | 1-1/16-12 | 15.5 | 1-3/16 | 30.16 | 1-1/8 | 28.57 | 24.4 | 68.8 | 37.3 | 79.0 | 47.5 | 25.8 | 16.8 | | |
| UBUA-1616S | 1 | 25.40 | 1 | 25.40 | 1-5/16-12 | 21.3 | 1-5/8 | 41.27 | 1-1/2 | 38.10 | 31.1 | 80.3 | 45.2 | 92.5 | 57.4 | 33.7 | 19.1 | | |

Dimensions are for reference only and are subject to change without prior notice.
E is minimum opening. F, G and L are typical finger tight.